

PAVING DETAILS

BRICKCAST PAVER STRENGTHS Class 25mPa Concrete Strength Class 35mPa Concrete Strength



Local labour is frequently called upon for laying and pre-operational tasks, particularly by contractors and the doit-yourself entrepreneurs. Men and women work side by side in preparing ground sites and the laying of pavers, compacting, sand filling and cementing edgings where necessary.




12-14 Torvale Crescent, Phoenix Industrial Park, Durban. P O Box 76801. Marbleray 4035






Our contracts support division is well equipped to handle all aspects of paving from the design stage right up to installation including, soil testing, earthworks, subsurface layers and the supply and laying of our products. We are also capable of handing turnkey projects to meet your aesthetic and cost requirements. We're only a phone call away.



A most efficient and robust dry stack retaining wall system. Depending on requirement, no foundation is necessary. For large constructions the bottom layer may be filled with concrete and rod options to create a suitable base structure. Coverage approximately 16 blocks per vertical square metre.



Brick colours illustrated may not necessarily match the actual brick colour. Colours should be chosen from the original brick samples



ROMAN PAVE COVERAGE: Approximately 38 pavers per m2 Allowance must be made for laying tolerance and edge cutting.

Colours: Charcoal, red, tan, grey, multiblend, terra-cotta, autumn, sunset, multi and dapple-multi. ROMANPAVE has an interlocking action increasing load carrying abilities.






COVERAGE

40 pavers per m2 Built in nib joining system allows for spread and self relocation, 60mm generally used in busy pedestrian thoroughfares, 80mm for heavy duty roadways. A durable fast laying interlocking paver, withstanding heavy loads and high traffic volumes








COVERAGE:

42 pavers per m2 Non slip surface wet or dry. Stylepave offers a multitude of colour combinations and designs to satisfy the most discerning.

COLOURS available to all pavers: Charcoal, red, tan, grey, multiblend, terra-cotta, autumn, sunset, multi and dapple-multi.





HONEYSTYLE COVERAGE: Hexagonal 24 pavers per m2 3 long halves per linear metre, 4 short halves per linear metre. Standard spacer nib fitting system ensures better interlocking against all surfaces. Non slip wet or dry.

Interwoven with STYLEPAVE, patterns are limitless.

COLOURS available to all pavers: Charcoal, red, tan, grey, multiblend, terra-cotta, autumn, sunset, multi and dapple-multi.



^{*} When estimating, allowance must be made for laying tolerance and edge cutting.